

# Data sheet

## TE 7000.440



### Main data:

<b>Model No.:</b>	TE 7000.440
<b>Designation:</b>	Network enclosure TE 7000, 24 U, WxD (mm) 600x800,
<b>Variant:</b>	n/a
<b>Packs of:</b>	1 ST
<b>W x H x D:</b>	600 mm x 1.200 mm x 800 mm
<b>Mounting surface:</b>	n/a
<b>Volume:</b>	624,00 dm <sup>3</sup>
<b>Net weight:</b>	71,44 kg
<b>EAN:</b>	4028177436480
<b>Customs number:</b>	85381000
<b>Protection categories:</b>	n/a

[You can find the product in Catalogue 32, page 741](#)

### Approbationen:

### Article features:

<b>Material</b>	sheet steel
	Surface finish
	powder-coated in RAL 7035
	Supply includes
	enclosure including levelling feet and spacers for raising the roof
	Technical specifications
	dimensions: WxHxD: 600x1200x800 mm
	available mounting height: 24 U
	protection category: IP 20

# Data sheet

## TE 7000.440



### **Texts for tenders:**

Network enclosure TE 7000

Screw-fastened, dismantling enclosure construction based on a self-supporting 482.6 mm (19.) mounting profile which also acts as the enclosure frame.

Modular roof and bottom frame connected to a supporting rack via imperial mounting frames. Plug-type, lockable side panels including security lock 3524E.

Glazed door at the front, with 4 mm safety glass, sheet steel door at the rear. Both including two-point locking rod, handle tray, safety lock 3524E, may be replaced by an Ergofrom-S handle for optionally integrating a semi-cylinder. Door hinges may be swapped, door opening angle 130°. Roof plate with integral brush strip, fan unit ready for connection including thermostat control may be retrofitted optionally. Interior installation is via two depth-adjustable 482.6 mm (19.) mounting frames with integral 25 mm system holes. The distance between the 482.6 (19.) angles is freely selectable.

Maximum load capacity of one mounting level is 200 kg, i.e. max. 400 kg for each rack.

The enclosure is bayable. A base/plinth may be mounted optionally.

**Supply includes: enclosure including levelling feet and spacers for raising the roof.**

**Material: sheet steel**

**Surface finish: powder-coated in RAL 7035**

**Dimensions: WxHxD: 600x1200x800 mm**

**Available mounting height: 24 U**

**Protection category: IP 20**